

# SERVICE PRO®

Premium Lubricants

## SERVICE PRO® PREMIUM dexos1™ FULL SYNTHETIC SAE 5W-30 MOTOR OIL



Manufactured with highly refined virgin base oils

### DESCRIPTION:

**SERVICE PRO® Premium dexos1™ Full Synthetic SAE 5W-30 Motor Oil** is a top tier, full synthetic motor oil specifically formulated and is licensed and approved by General Motors to meet the new GM global engine oil specification. GM license number RR1B0107032

**SERVICE PRO® Premium dexos1™ Full Synthetic SAE 5W-30 Motor Oil** is manufactured with advanced engineered additive chemistry and virgin synthetic base oils to ensure maximum performance in all driving conditions and at extreme temperatures.

**SERVICE PRO® Premium dexos1™ Full Synthetic SAE 5W-30 Motor Oil** is licensed API SN and ILSAC GF-5.

**SERVICE PRO® Premium dexos1™ Full Synthetic SAE 5W-30 Motor Oil** supersedes GM4718M and GM6094M specifications. This product is suitable for use in vehicles requiring GM4718M and GM6094M specifications.

### PERFORMANCE BENEFITS:

- Optimum corrosion and wear protection, engine cleaning and lubricating properties
- Increased compatibility with ethanol blended fuels
- Fully compatible with all synthetic, synthetic blend and convention motor oils
- Outstanding performance in low and high temperature performance and in all driving conditions

### TYPICAL PROPERTIES:

SAE Grade	5W-30
API Gravity @ 60°F	34.6
Sp. Gr. @ 60°F	0.08519
Flash, COC, °F	448
Pour Pt., °F	-30
Viscosity,	
cSt @ 40° C	53.7
cSt @ 100° C	10.0
Viscosity Index	177
API Performance	SN



Updated: 04/2011

SPWNDEXOS1

# SERVICE PRO®

## Premium Lubricants

### SERVICE PRO® PREMIUM FULL SYNTHETIC SAE 5W-40 MOTOR OIL

Manufactured with highly refined virgin base oils and licensed additive systems

**DESCRIPTION:**

SERVICE PRO® Premium Full Synthetic SAE 5W-40 is a top tier, high detergent automotive engine oil specially formulated to meet the stringent lubrication requirements of today's engines. Synthetic base oil combined with carefully selected additive packages to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish.

SERVICE PRO® Premium Full Synthetic SAE 5W-40 meets or exceeds the requirements of ACEA A3/ B4-04, BMW Longlife-01, Mercedes-Benz MB 229.3, 229.5, Porsche, Volkswagen VW 502 00/505 00, and VW 503 01. SERVICE PRO® Premium Full Synthetic SAE 5W-40 meets API Service Category SM.

**PERFORMANCE  
BENEFITS:**

- Our highest level of protection for thermal and oxidation stability
- Formulated for extreme driving conditions
- Outperforms conventional and synthetic blends
- Outstanding low and high temperature performance

TYPICAL PROPERTIES:	SAE Grade	5W-40
	API Gravity @ 60°F	35.0
	Sp. Gr. @ 60°F	0.852
	Flash, COC, °F	405
	Pour Pt., °F	-35
	Viscosity,	
	cSt @ 40°C	86.0
	cSt @ 100°C	14.2
	Viscosity Index	171



Updated: 02/11

SPWNFS5W40

# SERVICE PRO®

## Premium Lubricants

## SERVICE PRO® PREMIUM FULL SYNTHETIC MOTOR OILS

Manufactured with highly refined virgin base oils and licensed additive systems

**DESCRIPTION:** SERVICE PRO® Premium Full Synthetic GF-5 Motor Oils are top tier, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. Synthetic base oils combine with carefully selected additive packages to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish.

SERVICE PRO® Premium Full Synthetic GF-5 Motor Oils meet or exceed the requirements of GM 6094M and Ford WSS-M2C945-A (SAE 5W-20), Chrysler MS-6395 (SAE 0W-20). Meets Toyota Specifications, and Honda Service Fill Specifications All grades meet or exceed API Service Category SN, SM, SL, SJ and comply with ILSAC GF-5 requirements.

**PERFORMANCE  
BENEFITS:**

- Our highest level of protection for thermal and oxidation stability
- Formulated for extreme driving conditions
- Outperforms conventional and synthetic blends
- Outstanding low and high temperature performance
- ILSAC GF-5 Resource Conserving

TYPICAL PROPERTIES:	SAE Grade	0W-20	5W-20	10W-30
API Gravity @ 60°F		34.9	32.6	33
Sp. Gr. @ 60°F		0.8504	0.8478	0.852
Flash, COC, °F		405	405	405
Pour Pt., °F		-48	-40	-35
Viscosity,				
cSt @ 40°C		45	43.3	62.8
cSt @ 100°C		8.5	7.8	10.5
Viscosity Index		170	150	156
Zinc, Wt. %		0.0856	0.0836	0.082
Phosphorus, Wt. %		0.0767	0.0768	0.0746
API Performance		SN	SN	SN



Updated: 2/11

SPWNFSMO